

600V N-Channel Super Junction MOSFE
MAIN CHARACTERISTICS


I_D	7 A
V_{DSS}	600V
$R_{DS(on)-typ}(@V_{GS}=10V)$	< 600mΩ (Type:510mΩ)

Application

- ◆Solar inverters
- ◆LCD/LED/PDP TV
- ◆Telecom/Server Power supplies
- ◆AC-DC Power Supply

MECHANICAL DATA

- ◆Case: Molded plastic
- ◆Mounting Position: Any
- ◆Molded Plastic: UL Flammability Classification Rating 94V-0
- ◆Lead free in compliance with EU RoHS 2011/65/EU directive
- ◆Solder bath temperature 275°C maximum,10s per JESD 22-B106


Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Symbols	Value		Units
		220F	252/251	
Drain-Source Voltage	V_{DS}	600		V
Gate - Source Voltage	V_{GS}	±30		V
Continuous Drain Current	I_D	7		A
Pulsed Drain Current(note1)	I_{DM}	24		A
Power Dissipation	P_D	28	64	W
Single Pulse Avalanche Energy(note1)	E_{AS}	129		mJ
Operating Temperature Range	T_J	-50 to +150		°C
Storage Temperature Range	T_{STG}	-50 to +150		°C
Thermal Resistance, Junction-to-case	$R_{\theta JC}$	4.8	1.97	°C/W
Thermal Resistance, Junction ambient	$R_{\theta JA}$	62		°C/W







Note1:Pulse test: 300 μs pulse width, 2 % duty cycle

Maximum Ratings at Tc=25°C unless otherwise specified






Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	BV_{DSS}	600	-	-	V
Drain-Source Leakage Current	$V_{DS}=600V, V_{GS}=0V$	I_{DSS}	-	-	1	μA
Gate-Source Leakage	$V_{GS}=\pm 30V, V_{DS}=0V$	I_{GSS}	-	-	± 100	nA
Gate- Source Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	$V_{GS(th)}$	2	-	4	V
Drain-Source On State Resistance	$V_{GS}=10V, I_D=3.5A$	$R_{DS(ON)}$	-	510	600	m Ω
Forward Transconductance	$V_{DS}=5V, I_D=2A$	g_{fs}	-	-	8	S
Input Capacitance	$V_{DS}=50V$ $V_{GS}=0V$ $f=1MHz$	C_{iss}	-	471	-	PF
Output Capacitance		C_{oss}	-	35	-	
Reverse Transfer Capacitance		C_{rss}	-	1.7	-	
Turn-on delay time(note2)	$V_{DD}=325V$ $V_{GS}=10V$ $R_G=25\Omega$ $I_D=7A$	$t_{d(on)}$	-	17	-	nS
Rise Time(note2)		T_r	-	26	-	
Turn-Off Delay Time(note2)		$t_{d(OFF)}$	-	53	-	
Fall Time(note2)		t_f	-	38	-	
Total Gate Charge(note2)	$V_{DS}=520V$ $V_{GS}=10V$ $I_D=7A$	Q_g	-	13	-	nC
Gate-to Source Charge(note2)		Q_{gs}	-	2.1	-	
Gate-Drain Charge(note2)		Q_{gd}	-	6.9	-	
Maximun Body-Diode Continuous Current		I_S	-	-	7	A
Maximun Body-Diode Pulsed Current(Note2)		I_{SM}	-	-	24	A
Drain-Source Diode Forward Voltage	$T_J=25^\circ C, I_S=3.5A, V_{GS}=0V$	V_{SD}	-	-	1.4	V

 Note2:Pulse test: 300 μs pulse width, 2 % duty cycle


Ratings and Characteristic Curves



Package Outline Dimensions Millimeters



Marking Diagram



Ordering information


Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW60R600AF	TO-220F	0.06oz(1.74g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

Package Dimensions

TO-220F

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.50	4.90	0.177	0.193
A1	2.34	2.74	0.092	0.108
A2	2.66	2.86	0.105	0.113
b	0.75	0.85	0.030	0.033
b1	1.24	1.44	0.049	0.057
c	0.40	0.60	0.016	0.024
D	10.00	10.32	0.394	0.406
E	15.75	16.05	0.620	0.632
e	2.44	2.64	0.096	0.104
e1	4.88	5.28	0.192	0.208
F	3.10	3.5	0.122	0.138
L	13.50	13.90	0.531	0.547
L1	2.90	3.30	0.114	0.130
Φ	3.10	3.30	0.122	0.130

Marking Diagram



Ordering information


Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW60R600AMJ	TO-251S	0.011oz(0.32g)	80pcs/tube	4000pcs/box 24000pcs/Carton

Package Dimensions

TO-251S

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.1	2.5	0.083	0.098
A1	6.3	6.9	0.248	0.271
A2	0.9	1.1	0.035	0.043
A3	TYP0.5		TYP0.019	
b	0.6	0.8	0.024	0.031
c	0.4	0.5	0.015	0.020
D	5.3	5.5	0.209	0.217
D2	3.65	4.05	0.144	0.159
E	5.8	6.4	0.228	0.252
E2	0.9	1.4	0.035	0.055
e	TYP2.29		TYP0.090	
e1	TYP4.58		TYP0.180	
L	3.7	4.3	0.146	0.169

Marking Diagram



Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW60R600AD	TO-252	0.011oz(0.32g)	2500pcs/reel	5000pcs/box 25000pcs/Carton

Package Dimensions

TO-252

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.50	0.087	0.098
A1	0.00	0.12	0.000	0.005
A2	2.20	2.40	0.087	0.094
B	1.20	1.60	0.047	0.063
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
c	0.40	0.60	0.016	0.024
c1	0.40	0.60	0.016	0.024
D	6.35	6.65	0.250	0.262
D1	5.20	5.40	0.205	0.213
E	5.40	5.70	0.213	0.224
e	2.20	2.40	0.087	0.094
e1	4.40	4.80	0.173	0.189
L	10.00	11.00	0.393	0.433
L1	2.70	3.10	0.106	0.122
L2	1.40	1.80	0.055	0.071
L3	0.90	1.50	0.035	0.059

Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.