


-60V P-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS

I_D	-6A
V_{DSS}	-60V
R_{DS(on)-typ(@V_{GS}=-10V)}	< 90mΩ (Type:80 mΩ)

Application

- ◆ Battery protection
- ◆ Load switch
- ◆ Automotive lighting



Marking Code	
YFW6P06MI	6P06-13

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Symbols	Value	Units
Drain-Source Voltage	V_{DS}	-60	V
Gate - Source Voltage	V_{GS}	±20	V
Continuous Drain Current, V _{GS} @ -10V ¹ @T _A =25°C	I_D	-6	A
Continuous Drain Current, V _{GS} @ -10V ¹ @T _A =100°C	I_D	-4.3	A
Pulsed Drain Current ²	I_{DM}	-26	A
Single Pulse Avalanche Energy ³	E_{AS}	29.8	mJ
Avalanche Current	I_{AS}	-24.4	A
Total Power Dissipation ⁴ @T _A =25°C	P_D	31.3	W
Storage Temperature Range	T_{STG}	-55 to +150	°C
Operating Junction Temperature Range	T_J	-55 to +150	°C
Thermal Resistance Junction-Ambient ¹	R_{θJA}	125	°C/W
Thermal Resistance Junction-Case ¹	R_{θJC}	40	°C/W

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	BV_{DSS}	-60	-	-	V
BVDSS Temperature Coefficient	Reference to 25°C, $I_D=-1mA$	$\Delta BV_{DSS}/\Delta T_J$	-	-0.03	-	V/°C
Static Drain-Source On-Resistance ²	$V_{GS}=-10V, I_D=-3A$	$R_{DS(ON)}$	-	80	90	mΩ
	$V_{GS}=-4.5V, I_D=-2A$		-	100	115	
Gate -Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu A$	$V_{GS(th)}$	-1.2	-1.75	-2.5	V
$V_{GS(th)}$ Temperature Coefficient						
Drain -Source Leakage Current	$V_{DS}=-48V, V_{GS}=0V, T_J=25^\circ C$	I_{DSS}	-	-	1	μA
	$V_{DS}=-48V, V_{GS}=0V, T_J=55^\circ C$		-	-	5	
Gate-Source Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	I_{GSS}	-	-	±100	nA
Forward Transconductance	$V_{DS}=-5V, I_D=-3A$	g_{FS}	-	8.5	-	S
Total Gate Charge(-4.5V)	$V_{DS}=-48V$ $V_{GS}=-4.5V$ $I_D=-3A$	Q_g	-	12.1	-	nC
Gate-Source Charge		Q_{gs}	-	2.2	-	
Gate-Drain Charge		Q_{gd}	-	6.3	-	
Turn-on delay time	$V_{DD}=-15V$ $V_{GS}=-10V$ $R_G=3.3$ $I_D=-1A$	$t_{d(on)}$	-	9.2	-	nS
Rise Time		T_r	-	20.1	-	
Turn-Off Delay Time		$t_{d(OFF)}$	-	46.7	-	
Fall Time		t_f	-	9.4	-	
Input Capacitance	$V_{DS}=-15V$ $V_{GS}=0V$ $f=1.0MHz$	C_{iss}	-	1137	-	pF
Output Capacitance		C_{oss}	-	76	-	
Reverse Transfer Capacitance		C_{rss}	-	50	-	
Continuous Source Current ^{1,5}	$V_G=V_D=0V$, Force Current	I_S	-	-	-1.3	A
Diode Forward Voltage ²	$V_{GS}=0V, I_S=-1A, T_J=25^\circ C$	V_{SD}	-	-	-1.2	V

Note :

- 1、 The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、 The data tested by pulsed , pulse width $\cong 300\mu s$, duty cycle $\cong 2\%$
- 3、 The power dissipation is limited by 150°C junction temperature
- 4、 The data is theoretically the same as I D and I DM , in real applications , should be limited by total power dissipation.

Ratings and Characteristic Curves




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance v.s Gate-Source




Fig.3 Forward Characteristics of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ v.s T_J




Fig.6 Normalized $R_{DS(on)}$ v.s T_J

Ratings and Characteristic Curves




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform




Fig.11 Unclamped Inductive Switching Waveform

Ordering information


Package	Packing Description	Base Quantity	Packing Quantity
SOT23-3L	Tape/Reel, 7" reel	3000pcs/Reel	24000PCS/Box 120000PCS/Carton

Package Dimensions

SOT23-3L

Dim.	Millimeter (mm)		mil	
	Min.	Max.	Min.	Max.
A	1.05	1.25	41	49.2
A1	0.10		3.93	
A2	1.05	1.15	41	45
b	0.30	0.50	12	20
c	0.10	0.20	3.93	7.9
D	2.82	3.02	111	119
E	1.50	1.70	59	67
E1	2.65	2.95	104	116
e	0.95		37.4	
e1	1.80	2.00	71	78
L	0.30	0.066	12	26
Θ	8°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.