


High voltage surface mount diodes
Reverse Voltage – 8kV
Forward Current –50mA
FEATURES

- ◆High speed switching
- ◆High Current
- ◆High surge resisitivity for CRT discharge
- ◆High reliability design
- ◆High Voltage

Maximum Ratings and Characteristics

- ◆Absolute Maximum Ratings
- ◆Terminals: Pure tin plated leads, solderable per J-STD-002and JESD22-B102, E3 suffix for consumer grade, meet JESD201class 1A whisker test.
- ◆Polarity: Color band denotes cathode end

Pinning

Maximum rating (Ta=25°C unless otherwise noted)

Parameter		Symbol	YFW0850	Unit
Repetitive peak reverse voltage		V_{RRM}	8	KV
Average forward current	60Hz half-sine wave, Resistance load, Ta=25°C	$I_{F(AV)}$	50	mA
Surge(Non-repetitive)forward current	60Hz half-sine wave, 1cycle, Ta=25°C	I_{FSM}	10	A
Peak forward voltage	$I_{FM}=10mA$	V_{FM}	15	V
Peak reverse current $V_{RM}=V_{RRM}$	Ta=25°C	I_{RRM}	0.1	μA
	Ta=100°C		10	
Reverse recovery time	$I_F=2mA, I_{RM}=4mA$	T_{rr}	0.08	uS
Operating ambient temperature		T_a	-40 ~ +150	°C
Storage Temperature Range		T_{stg}	-40 ~ +150	°C
Virtual junction temperature		$T_{(vj)}$	150	°C

Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
DO-214AC SMA	Tape/Reel, 13"reel	5000PCS/Reel 50000PCS/Carton

Package Dimensions

DO-214AC SMA

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	1.9	2.45	75	96
D	4.0	4.5	157	181
E	2.5	2.8	100	110
H _E	4.7	5.2	185	205
c	0.15	0.31	6	12
e	1.3	1.8	51	71
g	0.9	1.5	35	59
b	0.05	0.2	2	7.9
a	0.3		12	

The recommended mounting pad size



Unit : $\frac{\text{mm}}{\text{mil}}$

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.