

50A GLASS PASSIVATED BRIDGE RECTIFIER Reverse

Voltage - 800 to 1600 V

Forward Current – 50A

FEATURES


- ◆ Surge overload rating-500 amperes peak
- ◆ Polarity:As marked on body
- ◆ Ideal for printed circuit board
- ◆ Plastic material has U/L

The flammability classification 94V-0

- ◆ Reliable low cost construction utilizing molded plastic technique

MECHANICAL DATA

- ◆ Case: SGBJ
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026




Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.


Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	SGBJ5008	SGBJ5010	SGBJ5012	SGBJ5014	SGBJ5016	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	800	1000	1200	1400	1600	V
Maximum RMS voltage	V_{RMS}	900	1100	1300	1500	1700	V
Maximum DC Blocking Voltage	V_{DC}	800	1000	1200	1400	1600	V
Maximum Average Forward Rectified Current	$I_{(AV)}$	50					A
Peak forward surge current single half sine-wave superimposed on rated load (JEDEC Method) 50Hz $T_j=25^{\circ}C$	I_{FSM}	500					A
Forward Voltage per element @ $I_F=25A$ DC	V_F	1.10					V
Maximum reverse current at rated Blocking voltage per leg $T_j=150^{\circ}C$	I_{RRM}	3					mA
Rating for fusing (t=1~10ms)	I^2t	1200					A ² S
A.C.50/60Hz;R.M.S.;1min	Viso	2500					V
Mounting Torque (Recommended torque:0.65 N· m)	Ms	0.8					N· m
Approximate Weight	Wt	10					g
Maximum thermal resistance per (1) tpotar ldiode	$R_{\theta JC}$	9/1.5					°C/W
Operating and Storage Temperature Range	T_j, T_{stg}	-40 ~ +150					°C


RATINGS AND CHARACTERISTIC CURVES



T_C , TEMPERATURE (°C)
Fig.1 Forward Current Derating Curve




V_F , INSTANTANEOUS FWD VOLTAGE (V)
Fig.2 Maximum Forward Characteristics, per element



NUMBER OF CYCLES
Fig.3 Max Non-Repetitive Surge Current

Marking Diagram



Ordering information

Package	Packing Description	Packing Quantity
SGBJ	bulk	100PCS/Box 1000PCS/Carton

Package Dimensions

SGBJ

Dim.	Millimeter(mm)		DimensionsinInch	
	Min.	Max.	Min.	Max.
A	34.50	35.50	1.36	1.40
B	24.50	25.50	0.96	1.00
C	2.90	3.50	0.11	0.14
D	16.60	17.60	0.65	0.69
E	3.70	4.30	0.15	0.17
F	2.20	2.80	0.09	0.11
G	2.00	2.60	0.08	0.10
H	0.90	1.10	0.04	0.04
I	7.20	7.80	0.28	0.31
J	4.30	4.90	0.17	0.19
K	3.40	4.00	0.13	0.16
L	0.20	0.80	0.01	0.03
M	13.80	14.40	0.54	0.57
N	2.50	2.90	0.10	0.11
O	0.55	0.75	0.02	0.03

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.