

Surface Mount Glass Passivated Standard Rectifier

Reverse Voltage - 700 V

Forward Current - 100mA


FEATURES

- ◆ For surface mounted applications
- ◆ Low profile package
- ◆ Easy to pick and place
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives
- ◆ Applied in LED lighting

MECHANICAL DATA

- ◆ Case: SOD-523
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026

Pinning



Marking Code

SGP7A	G7
--------------	-----------

Maximum Ratings(Ta =25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	700	V
Maximum DC Blocking Voltage	V_{DC}	700	V
Verage Rectified Output Current	I_F	100	mA
Non-Repetitive Peak Forward Surge Current at t=8.3ms	I_{FSM}	3.5	A
Operating Temperature Range	T_J	-55 to 150	°C
Storage Temperature Range	T_{STG}	-55 to 150	°C

ELECTRICAL CHARACTERISTICS (TA = 25°C unless otherwise noted)

Parameter	Test conditions	Symbol	Min	Typ	Max	Unit
Forward Voltage	$I_F=50mA$	V_F	-	-	1.1	V
Reverse Leakage Current	$V_R=700V, T_a=25^{\circ}C$	I_R	-	-	5	uA
Junction Capacitance	$V_R=0V, f=1MHz$	C_j	-	-	5	pF

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics





Fig.4 Typical Junction Capacitance



Ordering information

Package	Packing Description	Packing Quantity
SOD-523	Tape/Reel, 7" reel	3000PCS/Reel 120000PCS/Carton

Package Dimensions

SOD-523

Top view of the component. Dimension A is the height. HE is the total width. C is the thickness of the base. A note indicates 'ALL ROUND' for the corners.


Side view of the component. Dimension A is the height. E is the width of the main body. P is the radius of the top edge.

Bottom view of the component. D is the width of the main body. E is the height of the main body. e is the height of the base. L is the width of the base.

Bottom view of the component. N is the width of the main body. L is the width of the base. The text '底视图' and 'bottom view' are present.

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	0.51	0.77	20	30
e	0.25	0.35	10	14
C	0.08	0.15	3	6
D	1.10	1.30	43	51
E	0.75	0.99	30	39
HE	1.50	1.70	59	67
N	0.35ref		14ref	
L	0.2ref		8ref	
P	R0.1 ALL ROUND		R4.0 ALL ROUND	
∠	10°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.