

10.0A Single-Phase GLass Passivated Fast Recovery Bridge Rectifiers

Reverse Voltage - 1000 V


Forward Current - 10.0A

FEATURES

- ◆Glass passivated junction
- ◆The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- ◆Suge overload ratings to 200 amperes peak
- ◆Ideal for printed circuit board application
- ◆High temperature soldering guaranteed 265°C/10 seconds at 5 lbs(2.3kg)tension

MECHANICAL DATA

- ◆Case:HBS
- ◆Terminals:Platde leads solderable per MIL-STD-750, Method 2026
- ◆Polarity:Polarity symbols molded or Marked on body
- ◆Mounting Position:Any
- ◆Weight:0.015ounce,0.38 grams(approx)



Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter		Symbols	RHBS1010	Units
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	1000	V
Maximum RMS Voltage		V_{RMS}	700	V
Maximum DC Blocking Voltage		V_{DC}	1000	V
Maximum average forward rectified output current at	$T_A=100^{\circ}C$	$I_{F(AV)}$	10.0	A
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave, Superimposed on Rated Load (JEDEC Method)		I_{FSM}	220	A
I^2t Rating for Fusing ($t<8.3ms$)		I^2t	200.9	A ² S
Max Instantaneous forward voltage drop per diode	@ $I_F=1.0A$	V_F	0.90	V
	@ $I_F=5.0A$		1.15	
	@ $I_F=10.0A$		1.30	
Reverse Current at Rated DC Blocking Voltage	$T_A=25^{\circ}C$	I_R	5	μA
	$T_A=125^{\circ}C$		100	
Maximum reverse recovery time ($I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$)		T_{rr}	500	ns
Thermal resistance	Between Junction and Ambient	$R_{\theta JA}$	55	$^{\circ}C/W$
	Between Junction and Lead	$R_{\theta JL}$	14	
	Between Junction and Case	$R_{\theta JC}$	8	
Operating and Storage Temperature Range		T_j, T_{stg}	-55 to +150	$^{\circ}C$

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)

FIG.1-DERATING CURVE FOR OUTPUT RECTIFIED




FIG.3-TYPICAL REVERSE CHARACTERISTICS




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.4-TYPICAL FORWARD CHARACTERISTICS







FIG.5-Diagram of circuit and Testing wave form of reverse recovery time



Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
HBS	Tape/Reel, 13" reel	2500PCS/Reel 25000PCS/Carton

Package Dimensions

HBS

Dim.	Millimeter(mm)		Dimensions inInch	
	Min.	Max.	Min.	Max.
A	10.0	10.4	0.39	0.41
B	6.9	7.3	0.27	0.28
C	1.4	1.7	0.06	0.07
D	9.6	10.2	0.37	0.40
E	4.9	5.3	0.19	0.20
F	1.3	1.7	0.05	0.06

The recommended mounting pad size



Millimeter(mm)	
DIM	MIN
P0	5.10
P1	9.30
L	1.60
W	1.00

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.